

LAMIERE IN ACCIAIO INOSSIDABILE

Spessore mm	Peso kg/m ²	Dimensioni mm				
		1000 x 2000	1250 x 2500	1500 x 3000	2000 x 4000	2000 x 6000
		Peso Kg				
0,50	3,93	7,86	12,28	17,69	31,44	47,16
0,60	4,71	9,42	14,72	21,20	37,68	56,52
0,80	6,28	12,56	19,63	28,26	50,24	75,36
1	7,85	15,70	24,53	35,33	62,80	94,20
1,20	9,42	18,84	29,44	42,39	75,36	113,04
1,50	11,80	23,60	36,88	53,10	94,40	141,60
2,00	15,70	31,40	49,06	70,65	125,60	188,40
2,50	19,60	39,20	61,25	88,20	156,80	235,20
3,00	23,60	47,20	73,75	106,20	188,80	283,20
4,00	31,40	62,80	98,13	141,30	251,20	376,80
5,00	39,20	78,40	122,50	176,40	313,60	470,40
6,00	47,10	94,20	147,19	211,95	376,80	565,20
8,00	62,80	125,60	196,25	282,60	502,40	753,60
10,00	78,50	157,00	245,31	353,25	628,00	942,00
12,00	94,20	188,40	294,38	423,90	753,60	1130,40
15,00	117,80	235,60	368,13	530,10	942,40	1413,60

AISI 304	F1	Laminato a caldo, ricotto e decapato
	2B	Laminato a freddo, decapato, skinpassato
	F7	Satinat GR.220/240
	BA	Lucidato a specchio sui 2 lati
	SB	Sotch-brite
* finiture superficiali speciali a richiesta		
AISI 316	a richiesta	
AISI 430	a richiesta	