



UNI EN 10297

TUBI API

Ø pollici	Ø esterno mm	Spessore mm	Peso Kg/m	Norme API	Classe	Schedula
1/8	10,3	1,73	0,37	5L	STD	40
		2,41	0,47	5L	XS	80
		2,24	0,63	5L	STD	40
1/4	13,7	3,02	0,80	5L	XS	80
		2,31	0,80	5L	STD	40
		3,20	1,10	5L	XS	80
3/8	17,1	2,77	1,27	5L	STD	40
		3,73	1,62	5L	XS	80
		4,78	1,95			160
1/2	21,3	2,87	1,69	5L	STD	40
		3,91	2,20	5L	XS	80
		5,56	2,90			160
3/4	26,7	3,38	2,50	5L	STD	40
		4,55	3,24	5L	XS	80
		6,35	4,24			160
1	33,4	3,56	3,39	5L	STD	40
		4,85	4,47	5L	XS	80
		6,35	5,61			160
1 1/4	42,2	3,68	4,07	5L	STD	40
		5,08	5,41	5L	XS	80
		7,14	7,25			160
1 1/2	48,3	3,91	5,44	5L SLX	STD	40
		5,54	7,48	5L SLX	XS	80
		8,74	11,11			160
2	60,3	11,07	13,45	5L SLX	XXS	
		5,16	8,63	5L SLX	STD	40
		7,01	11,41	5L SLX	XS	80
2 1/2	73	9,53	14,92			160
		14,02	20,39	5L SLX	XXS	
		5,49	11,29	5L SLX	STD	40
3	88,9	7,62	15,27	5L SLX	XS	80
		11,13	21,33			160
		15,24	27,68	5L SLX	XXS	
3 1/2	101,6	5,74	13,57	5L SLX	STD	40
		8,08	18,63	5L SLX	XS	80
		6,02	16,07	5L SLX	STD	40
4	114,3	8,56	22,32	5L SLX	XS	80
		11,13	28,32	5L SLX		120
		13,49	33,54	5L SLX		160
5	141,3	17,12	41,03	5L SLX	XXS	
		6,56	21,75	5L S	STD	40
		9,52	30,97	5L X	XS	80
6	168,3	12,70	40,28	5L		120
		15,88	49,09	5L		160
		19,05	57,42	5L	XXS	
8	219,1	7,11	28,26	5L SLX	STD	40
		10,97	42,56	5L SLX	XS	80
		14,27	54,20	5L SLX		120
10	273	18,26	67,56	5L SLX		160
		21,95	79,22	5L	XXS	
		6,35	33,31	5L SLX		20
12	323,9	7,04	36,81	5L SLX		30
		8,18	42,55	5L SLX	STD	40
		10,31	53,08			60
14	355,6	12,70	64,64	5L SLX	XS	80
		6,35	41,77	5L SLX		20
		7,80	51,03	5L SLX		30
16	406,4	9,27	60,29	5L SLX	STD	40
		12,70	81,55	5L SLX	XS	60
		15,09	96,01			80
18	457	18,26	114,75	5L SLX		100

Ø pollici	Ø esterno mm	Spessore mm	Peso Kg/m	Norme API	Classe	Schedula
12	323,9	6,35	49,72	5L SLX		20
		8,35	65,20	5L SLX		30
		9,52	73,80	5L SLX	STD	
		12,70	97,46	5L SLX	XS	
		14,27	108,96	5L SLX		60
14	355,6	17,48	132,08	5L SLX		80
		7,92	67,90	5L SLX		20
		9,53	81,33	5L SLX	STD	30
		12,70	107,39	5L SLX	XS	
		15,09	126,71			60
16	406,4	19,05	158,10	5L SLX		80
		23,83	194,96			100
		7,92	77,83	5L SLX		20
		9,52	93,27	5L SLX	STD	30
		12,70	123,30	5L SLX	XS	40
18	457	16,66	160,12			60
		7,92	87,71	5L SLX		20
		9,53	105,16	5L SLX	STD	
		11,13	122,38	5L SLX		30
		12,70	139,15	5L SLX	XS	
20	508	14,27	155,80	5L SLX		40
		19,05	205,74	5L SLX		60
		23,83	254,55			80
		9,53	117,15	5L SLX	STD	20
		12,70	155,12	5L SLX	XS	30
22	559	15,09	183,12		STD	40
		20,62	247,83	5L SLX		60
		26,19	311,17			80
		9,53	129,13	5L SLX	STD	20
		12,70	171,09	5L SLX	XS	30
24	610	22,23	294,25			60
		9,53	141,12	5L SLX	STD	20
		12,70	187,06	5L SLX	XS	
		14,27	209,64	5L SLX		30
		17,48	255,11	5L SLX		40
26	660	24,61	355,25			60
		9,53	152,87	5L SLX	STD	
		12,70	202,72	5L SLX	XS	20
28	711	9,53	164,85	5L SLX	STD	
		12,70	218,63	5L SLX	XS	20
		15,88	271,29	5L SLX		30
30	762	9,53	176,85	5L SLX	STD	
		12,70	234,68	5L SLX	XS	20
		15,88	292,20	5L SLX		30
32	813	9,53	188,82	5L SLX	STD	
		12,70	250,64	5L SLX	XS	20
		15,88	312,15	5L SLX		30
34	864	17,48	342,91	5L SLX		40
		9,53	200,31	5L SLX	STD	
		12,70	266,61	5L SLX	XS	20
36	914	15,88	332,12	5L SLX		30
		17,48	364,90	5L SLX		40
		9,53	212,56	5L SLX	STD	
38	965	12,70	282,27	5L SLX	XS	20
		15,88	351,70	5L SLX		30
		19,05	420,42	5L SLX		40